

应用范围

适用于车辆低压系统的连接线。

APPLICATIONS

Suitable for connection of autocar low-voltage system

电线结构

多股细裸束绞铜丝或镀锡铜丝导体；
汽车专用90°C PVC绝缘。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor;
Autocar special-purpose 90°C temperature resistant PVC
insulation

技术参数

☑ 温度范围：-40°C ~ +90°C
☑ 符合标准：DIN ISO 6722(德国)

TECHNICAL DATA

☑ Operating Temp.: -40°C ~ +90°C
☑ Governing Standards: DIN ISO 6722 (Germany)

导体截面 Cross Section mm ²	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.5	16/0.20	2.00	2.3	9.0
0.75	24/0.20	2.20	2.5	12.0
1	32/0.20	2.40	2.7	15.0
1.5	30/0.25	2.70	3.0	20.0
2	40/0.25	2.90	3.2	26.0
2.5	50/0.25	3.30	3.7	32.0
3	60/0.25	3.50	3.9	37.0
4	56/0.30	4.00	4.4	49.0
6	84/0.30	4.60	5.0	68.0
10	80/0.40	6.20	6.4	113
16	128/0.40	7.50	8.1	181
25	200/0.40	9.50	10.2	288
35	276/0.40	10.60	11.4	377
50	400/0.40	12.90	13.6	535
70	555/0.40	14.80	15.5	713