

FLYK 1.5mm² SHANGHAI HANKE WIRE CO., LTD.

应用范围

适用于车辆低压系统的连接线。

APPLICATIONS

Suitable for connection of autocar low-voltage system

电线结构

多股细裸束绞铜丝或镀锡铜丝导体；
汽车专用90°C PVC绝缘。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor;
Autocar special-purpose 90°C temperature resistant PVC insulation

技术参数

☞ 温度范围：-40°C ~ +90°C
☞ 符合标准：DIN ISO 6722(德国)

TECHNICAL DATA

☞ Operating Temp.: -40°C ~ +90°C
☞ Governing Standards: DIN ISO 6722 (Germany)

导体截面 Cross Section mm ²	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.5	28/0.15	2.00	2.3	9.0
0.75	42/0.15	2.20	2.5	12.0
1	57/0.15	2.40	2.7	15.0
1.5	84/0.15	2.70	3.0	20.0
2.5	140/0.15	3.50	3.9	32.0
4	1015/0.08	4.50	4.9	53.0
6	1543/0.08	5.30	6.0	76.0
10	2510/0.08	6.70	7.3	124
16	4033/0.08	8.20	8.8	198
25	3169/0.11	9.90	10.5	298