


交通运输电缆系列 CABLES FOR TRANSPORTATION INDUSTRY

FLRY-A 1.5mm² SHANGHAI HANKE WIRE CO., LTD.



FLRY-B 1.5mm² SHANGHAI HANKE WIRE CO., LTD.



应用范围

适用于车辆低压系统的连接线。

APPLICATIONS

Suitable for connection of autocar low-voltage system

电线结构

多股细裸束绞铜丝或镀锡铜丝导体；
专用薄壁型绝缘。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincooper conductor;
Autocar special-purpose thin-wall insulation

技术参数

🌡️ 温度范围：-40℃ ~ +105℃
📏 符合标准：DIN 72551 (德国)

TECHNICAL DATA

🌡️ Operating Temp.: -40℃ ~ +105℃
📏 Governing Standards: DIN 72551 (Germany)

(FLRY-A型)

导体截面 Cross Section mm ²	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.35	7/0.254	1.26	1.3	4.7
0.5	19/0.18	1.50	1.6	6.5
0.75	19/0.23	1.79	1.9	10.0
1	19/0.26	2.00	2.1	13.5
1.5	19/0.32	2.30	2.4	18.0
2	19/0.36	2.50	2.6	22.5
2.5	19/0.41	2.85	3.0	29.0

(FLRY-B型)

导体截面 Cross Section mm ²	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.35	12/0.20	1.33	1.4	5.4
0.5	16/0.20	1.54	1.6	6.5
0.75	24/0.20	1.84	1.9	9.5
1	32/0.20	1.98	2.1	12.0
1.5	30/0.25	2.30	2.4	17.0
2.5	50/0.25	2.90	3.0	28.5
4	56/0.30	3.54	3.7	47.0
6	84/0.30	4.18	4.3	65.5