

HDAV 1.25mm² SHANGHAI HANKE WIRE CO., LTD.

应用范围

适用于车辆需要加强绝缘和机械强度部位的低压系统的连接线。

APPLICATIONS

Suitable for connection of autocar low-voltage system requiring enhanced insulation and mechanical strength bearing capacity.

电线结构

多股细裸束绞铜丝或镀锡铜丝导体；
汽车专用PVC绝缘。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor;
Autocar special-purpose PVC insulation

技术参数

温度范围：80℃
符合标准：（日本）

TECHNICAL DATA

Operating Temp.: +80℃
Governing Standards: (Japan)

导体截面 Cross Section mm ²	导体结构 Conductor Structure 根数/单根直径 Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max O.D. mm	重量(近似) Approx. Weight Kg/Km
0.5	7/0.32	2.96	3.2	15.1
0.5f	20/0.18	2.95	3.2	14.6
0.75f	30/0.18	3.15	3.4	18.0
0.85	11/0.32	3.23	3.4	19.8
0.85	16/0.26	3.20	3.4	19.4
1.25	16/0.32	3.48	3.9	24.3
1.25f	50/0.18	3.47	3.9	24.7
2	26/0.32	3.90	4.4	33.9
2f	37/0.26	3.82	4.4	32.9