

国外标准电线电缆系列 FOREIGN STANDARDS-BASED WIRES & CABLES



应用范围
适用于吸尘器等电源线。

APPLICATIONS
For power cord of suction cleaner

电线结构
多股细裸束绞铜丝或镀锡铜丝导体；
PVC绝缘，PVC护套。

WIRE MAKE-UP
Multi-stranded bare copper/tincopper conductor
PVC insulation, PVC sheath

技术参数
① 温度范围：60℃(用户需要可生产75、90、105℃等级)
② 额定电压：300V
③ 符合标准：UL 62

TECHNICAL DATA
① Operating Temp.: 60℃ (75, 90, 105℃ products also available at your request)
② Rated Voltage: 300V
③ Governing Std.: UL 62

规格 Size 芯数 × AWG Core No. × AWG	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
2 × 18	2 × 41/0.16	5.95	6.5	53.3
2 × 16	2 × 66/0.16	6.59	7.1	70.4
3 × 18	3 × 41/0.16	6.28	6.7	63.8
3 × 16	3 × 66/0.16	6.97	7.5	86.2