

国外标准电线电缆系列 FOREIGN STANDARDS-BASED WIRES & CABLES

NISPT-1 60℃ 300V 2×18AWG SHHKW



应用范围

适用于小型电动工具等电源线。

APPLICATIONS

For power supply line of small-sized electric tools

电线结构

多股细裸束绞铜丝或镀锡铜丝导体;
PVC绝缘, PVC护套。

WIRE MAKE-UP

Multi-stranded bare copper/tincopper conductor
PVC insulation, PVC sheath

技术参数

- 温度范围: 60℃(用户需要可生产75、90、105℃等级)
- 额定电压: 300V
- 符合标准: UL 62

TECHNICAL DATA

- Operating Temp.: 60℃ (75, 90, 105℃ products also available at your request)
- Rated Voltage: 300V
- Governing Std.: UL 62

规格 Size 芯数 × AWG Core No. × AWG	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
NISPT-1				
2×20	2×26/0.16	2.62×4.82	2.9×5.3	22.7
2×18	2×41/0.16	2.92×5.42	3.2×6.0	30.5
3×20	3×26/0.16	2.62×7.02	2.9×7.7	33.2
3×18	3×41/0.16	2.92×7.92	3.2×8.7	44.8
NISPT-2				
2×18	2×41/0.16	3.68×7.07	4.1×7.8	41.9
2×16	2×66/0.16	4.00×7.67	4.4×8.4	59.7
3×18	3×41/0.16	3.68×10.46	4.1×11.5	57.7
3×16	3×66/0.16	4.00×11.42	4.4×12.6	82.1