

H05VV-F型(70℃ 300/500V) 聚氯乙烯绝缘及护套电缆
A05VV-F型(70℃ 300/500V) 聚氯乙烯绝缘及护套电缆
H05VV-F (70℃ 300/500V) PVC-insulated and Sheathed Cable
A05VV-F (70℃ 300/500V) PVC-insulated and Sheathed Cable



国外标准电线电缆系列 FOREIGN STANDARDS-BASED WIRES & CABLES

(H05VV-F)
CE 认可号:
CE100103002606

CE H05VV-F 300/500V 4×0.75mm² SHANGHAI HANKE WIRE CO., LTD.

应用范围

适用于安装电器装置、仪器仪表、电信设备、动力和照明等内部各部件的固定连接。

APPLICATIONS

Suitable for fixed wiring of electric appliances, instruments/gauges, telecommunication equipment, power and lighting.

电线结构

多股细裸束绞铜丝或镀锡铜丝导体;
PVC绝缘、护套。

WIRE MAKE-UP

Multi-stranded fine bare copper/tincopper conductor
PVC insulation and sheath

技术参数

- ① 温度范围: -30℃ ~ +70℃
- ② 额定电压: U₀/U 300/500V
- ③ 符合标准: VDE 0281
- ④ 导体标准: VDE 0295/IEC 60228 5类

TECHNICAL DATA

- ① Operating Temp.: -30℃ ~ +70℃
- ② Rated Voltage: U₀/U 300/500V
- ③ Governing Std.: VDE 0281
- ④ Conductor Std.: Category 5 in VDE 0295/IEC 60228

导体截面 Corss section 芯数 × mm ² Core No. × mm ²	导体结构 Conductor Structure 芯数 × 根数/单根直径 Core No. × Cond. No./O.D	标称外径 Nominal O.D. mm	最大外径 Max.O.D. mm	重量(近似) Approx. Weight Kg/Km
H05VV-F				
2×0.75	2×24/0.20	6.46	7.2	60.0
2×1	2×32/0.20	6.74	7.5	68.0
2×1.5	2×30/0.25	7.07	8.6	91.0
2×2.5	2×50/0.25	9.48	10.6	136
2×4	2×56/0.30	10.88	12.1	206
3×0.75	3×24/0.20	6.83	7.6	71.0
3×1	3×32/0.20	7.14	8.0	81.0
3×1.5	3×30/0.25	8.34	9.4	110
3×2.5	3×50/0.25	10.26	11.4	176
3×4	3×56/0.30	11.75	13.1	248
4×0.75	4×24/0.20	7.47	8.3	86.0
4×1	4×32/0.20	8.00	9.0	103
4×1.5	4×30/0.25	9.33	10.5	134
4×2.5	4×50/0.25	11.23	12.5	215
4×4	4×56/0.30	12.88	14.3	304
5×0.75	5×24/0.20	8.36	9.3	105
5×1	5×32/0.20	8.74	9.8	121
5×1.5	5×30/0.25	10.38	11.6	173
5×2.5	5×50/0.25	12.50	13.9	261
5×4	5×56/0.30	14.52	16.1	377
A05VV-F				
7×1	7×32/0.20	9.71	12.0	160
7×1.5	7×30/0.25	11.49	14.0	236
7×2.5	7×50/0.25	13.62	17.0	337